



## Ultracoat

A Polytetrafluoroethylene (P.T.F.E.) fortified paint sealant containing artificial gloss enhancers and antistatic polymer which protects the vehicle's finish from sun, salt, grease, tar, acid rain and industrial fallout, while sealing in a deep and durable shine.

<b>Gloss Level</b>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
<b>Buffability</b>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
<b>Durability</b>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

Ultracoat – (HSN – 3405 3000)

**Packing** 500ml, 2.5L, 40L, 200L

### Characteristics

- Milky white lotion
- Contains antistatic crosslinking polymer
- Enhances gloss and protects
- Extremely durable
- P.T.F.E. fortified

### Key Benefits

- Lotion formulation easy to apply and remove which saves time and effort.
- Polymer chemically bond to paint creating extremely durable protective layer.
- Produces a deep and rich shine.
- Protects finish from sun's ultra-violet rays.

### How to use

- **High Speed Buffer**
  - Dust off or wash your car to get rid of any dirt or dust particles.
  - Following steps to be done starting from the roof, proceeding to the hood, trunk and sides.
  - Apply a small amount of the product directly on the painted surface or on every quadrant of the polishing pad.
  - Buff a 2'X2' area by keeping the polishing pad flat on the surface, and applying even pressure until the product is dry.
  - Remove the residue with clean soft microfiber.
- **Orbital Buffer / Hand**
  - Dust off or wash your car to get rid of any dirt or dust particles.
  - Following steps to be done starting from the roof, proceeding to the hood, trunk and sides.
  - Apply product evenly over a painted surface with a moist polishing bonnet or applicator sponge.
  - Use even pressure in circular motion to remove swirls and minor scratches and allow it to dry to haze.
  - Remove the residue with clean soft microfiber.

### Notes

- Do not inhale/swallow.
- Avoid contact with skin and eyes.